

# FST-18H



## FTTx Active Cladding Alignment Fusion Splicer

Auto splice mode manifest user-friendly design

Dust-proof, water-proof, high-temperature resistance, adapting to various altitude and formidable nature conditions

4.3" high resolution color LCD touch screen, 380X magnification, visible clearly with bare eyes

Packed with detachable 5200mAh battery, more than 280 times of splicing and heating

3 high-power white LEDs and illuminated keypads simplifies your work at night

Detachable multifunction fixture, suitable for various fiber type

German CNC technique and integrated fiber-adjust frame, which make performance much stable

Built-in Japanese components and Korean chipset



3s Turn On



6s Fast Splicing



13s Heating



**STABLE  
INTELLIGENT  
ECONOMIC  
CONVENIENT**

Priority model for FTTx



# Splicer Master **FST-18H**

## Optical Fiber Fusion Splicer

Combining domestic with foreign technologies, Tumtec has been dedicated to providing professional optical fiber solution and become the renowned fusion splicer & fiber cleaver manufacturer for 16 years.

### Standard Accessories

Fusion splicer FST-18H*1
Fiber cleaver *1
Battery *1
Power adapter *1
AC power line *1
Back-up electrode *1
Cooling tray *1
Carrying case *1
Carrying strap *1
User manual *1
Splicing test report *1
Miller stripper *1
Drop cable stripper *1
Alcohol bottle *1



### Equipment Parameters

Model	FST-18H
Dimension	115W*160L*135H (excluding rubber bumper) / 120W*165L*135H (including rubber bumper)
Weight	1735G (with battery) / 1355G (without battery)
Number of Fiber	Single
Applicable Fibers	SM(ITU-T G.652& G.657)/MM(ITU-T G.651)/DS(ITU-T G.653)/NZDS(ITU-T G.655)
Compatible Fiber/Cable	0.25 - 3.0mm/Indoor Cable
Cleaved Length	Diameter: 0.125 - 1 mm/Cleave Length: 8-16mm
Cladding Diameter	80 - 150 μm
Splicing Mode	Pre-set 41 splicing modes, max 100 modes
Heating Mode	Pre-set 5 heating modes (20/30/40/50/60mm), max 100 modes
Typical Splice Loss	SM: 0.03dB / MM: 0.02dB/ DS: 0.05dB / NZDS: 0.05 dB/ G.657: 0.03dB (ITU-T Standard)
Return Loss	≥ 60dB
Lighting	3 White LEDs
Splicing Time	Quick mode: 6s
Estimated Splice Loss	Available
Heating Sleeve Length	20 - 60 mm
Heating Time	Quick heating time: 13s, typical heating time: 30s
Results Storage	20000 records & 200 images
Tension Test	1.96 - 2.25N
Operating Condition	Operating Altitude: 0 - 5000m above sea level, 0 - 95% relative humidity, - 10 ~ 50 °C, Max Wind 15m/s
Storage Condition	0 ~ 95% relative humidity, -40 ~ 80°C
Display	90° bi-directional view, 4.3" Color High Resolution Display
Fiber View & Magnification	X, Y, XY, X/Y: 380X Magnification
Power Supply	AC Input 100 - 240V, DC Input 12 - 15V
No. of Splice/Heating with Battery	5200mAh Battery Capacity, Typical 280 times (Splice + Heat)
Operating Methods	Button/Touch Screen
Automatic Calibration	Automatic arc calibration by air pressure and temperature
Electrode Life	5000 arcs
Terminal	Mini USB 2.0

Tumtec reserve the right to change the design, properties and products without notice. ©2018 print in China



Dirección: Calle México 1554 Edif. Chuquiago MZ-2.

Teléfono/Fax: (2)2-231-1125 / 211-4820  
E-mail: datel@entel.com

Cel.: 71521900 / 71535025  
Pagina web: www.datelsrl.com