


FST-V1



FTTX ACTIVE CLADDING ALIGNMENT FUSION SPLICER



Detachable Heat
Oven for SOC



Working at Height



Connect to Internet



Light Weight



COMPACT ACTIVE V-GROOVE FUSION SPLICER

LIGHT WEIGHT, COMPACT SIZE, HANDHELD FUSION SPLICER

SMART CONNECTING WITH INTERNET

3.5" HIGH RESOLUTION LCD TOUCH SCREEN WITH 380X MAGNIFICATION

GERMAN CNC TECHNIQUE AND INTEGRATED FIBER-ADJUST FRAME, WHICH MAKE PERFORMANCE MUCH STABLE

BUILT-IN JAPANESE COMPONENTS AND KOREAN CHIPSET

2 HIGH-POWER WHITE LEDS AND ILLUMINATED KEYPADS SIMPLIFIES YOUR WORK AT NIGHT

DUST PROOF, WATER PROOF, SHOCK PROOF AND HIGH TEMPERATURE RESISTANCE

FST-V1

STANDARD CONFIGURATION

Name	Model	Quantity	Name	Model	Quantity
Host machine	FSTV1	1pc	Carrying case	X103	1pc
Fiber cleaver	/	1pc	Alcohol bottle	/	1pc
Battery	TPW-45	1pc	Cooling tray	TP02	1pc
Spare electrode	E2	1 pair	Carrying Straps	/	1pc
Adapter	TPA150300	1pc	Test report	/	1pc
powercable	/	1pc	User Manual	/	1pc
Fiber stripper(optional)	CFS-2	1pc	Cleaning kitbag (optional)	/	1pc
Cable stripper(optional)	WX-1101	1pc	Rubber Blower (optional)	/	1pc
SOC fiber holder	/	1 pc	Working table (Optional)	/	1pc




LED Torch Light, Easy for Operation at Night



Carrying Bag or Carrying Case

EQUIPMENT PARAMETERS

Model	FST-V1
Applicable Fibers	SM(ITU-T G. 652&G.657),MM(ITU-T G.651),DS(ITU-T G.653),NZDS(ITU-T G655)
Compatible Fiber/Cable	0.25-3.0mm/Indoor Cable
Cleaved Length	Coating Diameter: 0.125-1mm/Cleave length:8-16mm
Splicing Mode	Preset 41 splicing modes, storable 100 modes
Typical Splice Loss	SM: 0.03dB/MM: 0.02dB/DS: 0.05dB/NZDS: 0.05dB/G657: 0.03dB (ITU-T Standard)
Return Loss	≥60db
Lighting	2 powerful white LEDs
Splicing Time	SM fast mode: 6s
Estimated Splice Loss	yes
Protection Sleeve Length	20-60mm
Heating tank	Preset 5 kinds of thermal heating tube: 20/30/40/50/60mm, Max 100 modes
Heating Time	Fast heating time: 13s, Typical Heating Time: 30s
Results Storage	20000 latest records & 200 images
Tension Test	1.5-2.0N
Display	3.5" high resolution display with touch screen
Fiber View & Magnification	X,Y,XY,X/Y:380×Magnification
Power Supply	AC Input 100-240V,DC Input 12-15V
Battery capacity	2200mAh battery capacity
Heating times	typical above 120 times(splicing+heating)
Operating Methods	Button/Touch Screen
Automatic Calibration	Automatic ARC calibration by air pressure and temperature
Electrode Life	5000 ARCS
Terminal	USB 2.0
Weight	1.15 KG (including rubber Bumper)
Dimension	132W*205L*98Hmm (including rubber Bumper)
Operating Condition	Operating altitude 0-5000m above sea level, 0-95% relative humidity-10~50°C, max wind 15m/s
Storage Condition	0~95% relative humidity, -40~80°C; battery storage: -20~30°C



Dirección: Calle México 1554 Edif. Chuquiago MZ-2.

Teléfono/Fax: (2)2-231-1125 / 211-4820
E-mail: datel@entel.com

Cel.: 71521900 / 71535025
Pagina web: www.datelsrl.com