



MAY11 Optical Power Meter



Feature:

- User calibration
- Wavelength memory function
- LED light for dark environment
- Suitable for SM and MM fibers
- Auto power-off
- Support frequency detection
- Low battery indication
- LCD color screen
- Both linear (mW) and non-linear (dBm)
- High capacity rechargeable lithium battery
- Detector head can be moved down for protection

Specification:

Model	MAY11A	MAY11B
Measuring Range	-70 to +10dBm	-50 to +26dBm
Calibrated Wavelength	850/980/1300/1310/1490/1550/1625nm	
Detector Type	InGaAs (300um)	
Resolution	Linear display: 0.1%, logarithmic display:0.01dBm	
Linearity	±5%	

Dirección: Calle México 1554 Edif. Chuquiago MZ-2

Teléfono/Fax: (2)2-231-1125 / 211-4820

E-mail: datel@entel.c

Cel.: 71521900 / 71535025

Pagina web: www.datelsrl.com



Continuous Working Time	18h
Connector	Universal 2.5mm (FC, SC, ST)
Charging Time	About 3 hours
Automatic Shutoff Time	10min
Tone Detection	CW, 270, 1k, 2kHz
Power supply	Rechargeable Lithium battery
Dimension	127*45*20mm
Packing Dimension	150*62*40mm
Net Weight	87g
Operating Temperature	-20 to +60°C
Storage Temperature	-25 to +70°C
Relative Humidity	0~95% (non-condensing)

Standard Accessory:

Item	Name	Quantity
1	Optical Power Meter	1pc
2	User Manual	1pc
3	USB Cable	1pc
4	Lithium Battery	1pc