



MSTronic Co., Ltd.

2F, 12, Gongshang Rd., Wugu Dist., New Taipei City, 248, Taiwan

TEL:886-2-2293-0159 FAX:886-2-2292-8851

E.MAIL: mse@mse.com.tw
WEB: <http://www.mse.com.tw>

MS-T100B

RJ11 Surge Protector

Feature

- + Shielded RJ11 jack and metal housing for EMI noise suppression
- + CAT C compatible
- + Cast aluminum construction
- + Integral mounting feet
- + Test Normal IEEE C62. 41-1991 Cat. C

Specification

Operating Voltage	VCC 24V(3,6),Line 48Vdc/90Vac(2,5)
Clamping Voltage	VCC 39V Line 170V
Max. Surge Discharge Current	5KA (8/20uS)
Peak Pulse Current	100A (10/1000uS)
Pin Protected	4 pin protected
Protection Mode	Differential & Common mode
Insulation Impedance	> 1000M Ohm
Max. Work Current	500mA
Data Rate	10 MHZ
Impulse protected Voltage	< 650V
Response Time	< 5 nS
Series Resistance	<5Ω
Operating Temperature	-40°C ~+85°C
Storage Temperature	-40°C ~+90°C
Operating Humidify	0~95% non condensing
Dimensions	82 x 25.4 x 25.4 mm (include bracket) 68 x 25.4 x 25.4 mm (main body)
Weight	68 g